


Four-Leg Solid state relays

4 single phase SSRs in a SC case - save place in control panels (width 45 mm).




PRODUCT REFERENCE	Switching Current	Switching voltage	Peak voltage	Control Voltage	Input R	I _{ft}	Dimensions mm	Led
SCQ842000	4x25A	12-280VAC	600V	3-32VDC	I <10mA	288A ² s	44,5x58,2x27	oui
SCQ842060	4x25A	12-280VAC	600V	3-32VDC	I <10mA	288A ² s	44,5x58,2x27	non

These products should be mounted on heatsink in order to reach nominal current.

Special Relays

Shunting relays



SAS Relays

Airport beacon relay.
If a lamp fails, the relay short circuit this lamp.
Different configurations available.

Dry contact relays



SG241010 relay

230VAC mains.
12A output voltage.
Control by PLA type insulated contact.
Typical applications : heating breaking, etc.

Flashing relays



ST Relay

ST645000: flashing 1/2Hz 230VAC 15A.
ST647000: flashing 1/2Hz 230VAC 25A.
ST323000: flashing 1/2Hz 30-60VDC 10A.

In addition to the very large range of solid state relays, **celduc®** design specific products according to the customers specifications or adapt products to the customers needs if prices and volumes can justify such developments.
Please do not hesitate to consult us.



4 SKL
Relays on PCB



This device using SSRs controls AC motors in hazardous area. Control by pushbutton with embedded magnet actuating Reed switches.



Solid state contactor for 3 phase motor.
Dry contact control
Spring terminals

celduc® relais is the specialist of typical customers applications.